

# Pencil Hitester

**HIOKI**



**PENCIL HITESTER 3246-60** CE  
Product warranty for 3 years  
Accuracy guaranteed for 1 year

CAT IV 300V, CAT III 600V



Cord length  
80 cm (2.62 ft.)



Test lead fits neatly  
into back of instrument

**Included accessories**

- Sleeves ( red, black @ 1 each)
- CR2032 coin type battery x1
- Instruction manual

Order code **3246-60**



Measurement parameters	DC Voltage	420.0 mV, 4.200 V, 42.00 V, 420.0 V, 600 V Accuracy: ±1.3% rdg. ±4 dgt.
	AC Voltage	4.200 V, 42.00 V, 420.0 V, 600 V Accuracy: ±2.3% rdg. ±8 dgt.
	Resistance	420.0 Ω, 4.200 kΩ, 42.00 kΩ, 420.0 kΩ, 4.200 MΩ, 42.00 MΩ Accuracy: ±2.0% rdg. ±4 dgt.
	Continuity check	Detection level: 50 Ω ±40 Ω or less
	Diode check	Judges the right direction only, Open terminal voltage 3.4 V or less
Other	Operating temperature	0°C to 40°C (non-condensating)
	Storage temperature	-20°C to 60°C (non-condensating)
	Power supply	CR2032 coin type battery x1
	Dimensions (W x H x D)	30 x 182 x 26.5 mm (1.18 x 7.17 x 1.04 in.)
Weight	80 g (2.8 oz.)	